

Bergen Cabling Uskjermet Patchesnor Cat6A 10 Gigabit



Karakteristikk

Kommunikasjonskabel for Horisontal innendørs installasjoner.

TIA/EIA-568B.2-1;ISO/IEO 11801; NEC/CEC
Fire protection – IEC60332-1 (CM)

Standarder

ANSI/TIA/EIA-568-C.2: T568A & T568B
ISO/IEC 11801: 8-position conductor/pair assignment (1-2/3-6/4-5/7-8)

Transmisjon egenskaper

NSI/TIA-568-C.2: category 6A (1-500 MHz) specifications

Kabel egenskaper

Construction:	4 pairs, 7 strands, 24 AWG, UTP	
Cable Type:	UTP Cat.6A Patch Cable	
Outer Cable Diameter:	5.8mm ± 0.2 mm	
Pair Identification:	Pair1= Blue/White	Pair2= Orange/White
	Pair 3= Green/White	Pair4= Brown/White
Outer Jacket:	LSZH-FR Jacket	

Plugg

Type: Unshielded RJ45 8P8C Modular Plug
Housing: UL listed 94V-0/1/2 flame retardant polycarbonate

Mekaniske egenskaper

Retention: 50 N (11 lbf) for 60±5 s
Mating cycle life: min 750 cycles
Tensile strength: ≥ 20 N per wire
Installation Temperature: 0°C to +60°C
Operating temperature: -20°C to +60°C
Minimum bend radius: 4 outer cable diameters

Bestillingsinformasjon

El Nr.	Part Name
6904243	Patchesnor Cat6A UTP hvit 0,2m
6904244	Patchesnor Cat6A UTP hvit 0,5m
6904245	Patchesnor Cat6A UTP hvit 1m
6904246	Patchesnor Cat6A UTP hvit 2m
6904247	Patchesnor Cat6A UTP hvit 3m
6904248	Patchesnor Cat6A UTP hvit 5m
6904249	Patchesnor Cat6A UTP hvit 10m
6904250	Patchesnor Cat6A UTP hvit 15m
6904251	Patchesnor Cat6A UTP hvit 20m