

Bergen Cabling skjermet Patchesnor Cat6A 10 Gigabit



Karakteristikk

Kommunikasjonskabel for Horisontal innendørs installasjoner.

TIA/EIA-568B.2-1;ISO/IEO 11801; NEC/CEC
Fire protection – IEC60332-1 (CM)

Standarder

ANSI/TIA/EIA-568-C.2: T568A & T568B
ISO/IEC 11801: 8-position conductor/pair assignment (1-2/3-6/4-5/7-8)

Transmisjon egenskaper

NSI/TIA-568-C.2: category 6A (1-500 MHz) specifications

Kabel egenskaper

Construction:	4 pairs, 7 strands, 26 AWG, SFTP	
Cable Type:	SFTP Cat.6A Patch Cable	
Outer Cable Diameter:	6.0mm ± 0.2 mm	
Pair Identification:	Pair1= Blue/White	Pair2= Orange/White
	Pair 3= Green/White	Pair4= Brown/White
Outer Jacket:	LSZH-FR Jacket	

Plugg

Type: Shielded RJ45 8P8C Modular Plug
Housing: UL listed 94V-0/1/2 flame retardant polycarbonate

Mekaniske egenskaper

Retention: 50 N (11 lbf) for 60±5 s
Mating cycle life: min 750 cycles
Tensile strength: ≥ 20 N per wire
Installation Temperature: 0°C to +60°C
Operating temperature: -20°C to +60°C
Minimum bend radius: 4 outer cable diameters

Bestillingsinformasjon

El Nr.	Part Name
6904252	Patchesnor Cat6A STP grå 0,2m
6904253	Patchesnor Cat6A STP grå 0,5m
6904254	Patchesnor Cat6A STP grå 1m
6904255	Patchesnor Cat6A STP grå 1,5m
6904256	Patchesnor Cat6A STP grå 2m
6904257	Patchesnor Cat6A STP grå 3m
6904258	Patchesnor Cat6A STP grå 5m
6904259	Patchesnor Cat6A STP grå 10m
6904260	Patchesnor Cat6A STP grå 15m
6904261	Patchesnor Cat6A STP grå 20m