

## Fiber adaptere SC/LC/ST



SC Duplex (blå-SM, beige-MM)



LC Duplex (blå-SM, beige-MM)



ST Simplex (gul-SM, sort-SM)



## Fiber Adaptere

---

Kvalitets fiber adaptere. LC singelmodus adapterne og LC Multimodus adapterne har en keramisk ferrul, SC og ST multimodus adapterne har en fosfor bronse ferrul.

## Spesifikasjoner

---

### Features

- Complies with IEC 61754-20
- High precision alignment sleeve
- Low insertion loss and high reconnectability
- REACH SvHC compliant
- Materials compliant to RoHS2

### Applications

- Telecommunications networks
- CATV, LAN, MAN and WAN application
- Data processing networks
- Cable television
- Fibre-To-The-Home
- Premises distribution

### Specification SC

	Ceramic	Phosphor Bronze	Conformance
Insertion Loss (Typ)	0.1dB	0.15dB	IEC 61300-3-4
Mating Durability	-	500	IEC 61300-2-2
Receptacle Retention Force	-	2N – 5.9N	IEC 61754-4
Operating Temperature -		-25 to +70, 12 cycles	IEC 61300-2-22

### Specification LC

DESCRIPTION	CERAMIC	CONFORMANCE
Insertion Loss (Typ)	0.1 dB	IEC 61300-3-4
Mating Durability	500	IEC 61300-2-2 IEC 61754-20
Receptacle Retention Force	1N - 2.5N	
Operating Temperature	-25 to +70, 12 cycles	IEC 61300-2-22

### Specification ST

OPTICAL PERFORMANCE	CERAMIC	PHOSPHOR BRONZE	CONFORMANCE
Insertion Loss (Typ)	0.1dB	0.15dB	IEC 61300-3-4
Mating Durability	500	500	IEC 61300-2-2
Receptacle Retention Force	2N - 5.9N	2N - 5.9N	IEC 61754-2
Operating Temperature	-25 to +70, 12 cycles	-25 to +70, 12 cycles	IEC 61300-2-22

## Bestillingsinformasjon

El Nr.	Part Name
6904272	Adapter SC duplex SM Blå
6904273	Adapter SC duplex MM Beige
6904274	Adapter LC duplex SM Blå
6904275	Adapter LC duplex MM Beige
6904276	Adapter ST SX SM Gul beskyttelse
6904277	Adapter ST SX MM Sort beskyttelse